



PRODUCT INFORMATION LiteBench-ST_TY_US - 20.01.2021 - www.vs-furniture.com

LiteBench-ST Stackable bench.

Frame made from welded round tubular steel legs with all-round rectangular tubular steel top frame, all powdercoated. Because the inner and outer legs are arranged in pairs, the bench is stackable. What is more, they can be rotated to form continuous rows. The edge of the top frame is equipped with stacking and glide protection. Benches with glide elements for hard or soft floorings or with 2C universal glide elements.

Seat sizes in 6 fixed heights in accordance with DIN EN 1729.

Seat top Consisting of a CDF or chipboard top and glued (KU) plastic border. Available with edged or rounded corners as required.

	Size as per DIN EN 1729 $h = 12^{1/4} = 2$ $h = 13^{3/4} = 2$ $h = 13^{5} = 4$ h = 17 = 5 $h = 18^{1/6} = 6$ $h = 20^{1/6} = 7$	w-d footprint
LiteBench-ST	d = 13¾	31083 31084 31085 31086 31085
	W	591/8 67 747/8 823/4 905/
	for table w	63 707/8 783/4 865/8 941/
	h DIN EN	2:3:4:5:6:7
	max. stacking height	4
	max. stacking height w*	65 727/8 803/4 885/8 961/
	max. stacking height d*	17
	Weight lb	46,2 54,0 61,7 69,4 77,